



## PRIMAVERA 50 4T3V - TECHNICAL SPECIFICATIONS

<b>ENGINE</b>	3-valve 4-stroke single cylinder i-get catalysed
<b>DISPLACEMENT</b>	49.9 cc
<b>BORE X STROKE</b>	39 mm x 41,8 mm
<b>MAX POWER AT THE CRANK SHAFT</b>	3.2 HP - at 7,500 rpm
<b>MAX TORQUE</b>	2.2 ft-lb at 7,000 rpm
<b>CONSUMPTION</b>	80.91 mpg
<b>CO2 EMISSIONS COMPLIANCE</b>	65 g/km
<b>FUEL SYSTEM</b>	Electronic Injection
<b>COOLING</b>	Forced air
<b>STARTER</b>	Electric
<b>GEARBOX</b>	CVT automatic with torque server
<b>CLUTCH</b>	Automatic dry centrifugal with shock absorbers
<b>LOAD-BEARING STRUCTURE</b>	Sheet steel shell with welded structural reinforcements
<b>FRONT SUSPENSION</b>	Single arm with helical spring and hydraulic shock absorber
<b>REAR SUSPENSION</b>	Helical spring with single hydraulic shock absorber
<b>FRONT BRAKE</b>	Stainless steel Ø 220 mm disc with hydraulic control
<b>REAR BRAKE</b>	Ø 140 mm drum with mechanical control
<b>ABS/ASR SYSTEM</b>	-
<b>FRONT TIRE</b>	Tubeless 110/70 - 12"
<b>REAR TIRE</b>	Tubeless 120/70 - 12"
<b>LENGTH/WIDTH/WHEELBASE</b>	73.6 / 28.9 / 52.3 in
<b>SEAT HEIGHT</b>	31.1 in
<b>FUEL TANK CAPACITY</b>	2.1 gal
<b>EMISSIONS COMPLIANCE</b>	Euro 4