



TYPHOON 50 – TECHNICAL SPECIFICATIONS

ENGINE	Single cylinder two-stroke
CAPACITY	49 cc
BORE X STROKE	40 mm x 39,3 mm
POWER	2.2 kW - 3 HP - at 7000 rpm
TORQUE	3 Nm at 6500 rpm
FUEL SYSTEM	Carburettor
COOLING SYSTEM	Air
LUBRIFICATION	Automatic mixer controller according to throttle opening and engine speed
STARTER	Electric and kick starter
TRANSMISSION	CVT with torque server
CLUTCH	Automatic centrifugal dry clutch
FUEL CONSUMPTION (WMTC CYCLE)	26.3 km/l
CO² EMISSIONS	85 g/km
EMISSION COMPLIANCE	Euro 4
CHASSIS	High strength reinforced tubular steel single cradle frame
FRONT SUSPENSION	Hydraulic telescopic fork
REAR SUSPENSION	Hydraulic shock absorber
FRONT BRAKE	Hydraulically operated 220-mm disc
REAR BRAKE	140 mm drum
LENGTH / WIDTH	1945 mm / 690 mm
WHEEL BASE	1360mm
SEAT HEIGHT	789mm
FUEL TANK CAPACITY	6.5 litres
FRONT TYRE	Tubeless 120/80 - 12"
REAR TYRE	Tubeless 130/80 - 12"