



SPRINT 150 S 3V ABS - TECHNICAL SPECIFICATIONS

ENGINE	3-valve 4-stroke single cylinder i-get catalysed
DISPLACEMENT	155 cc
BORE X STROKE	58 mm x 58,6 mm
MAX POWER AT THE CRANK SHAFT	12.9 HP - at 7,750 rpm
MAX TORQUE	9.4 ft-lb at 6,500 rpm
CONSUMPTION	94.79 mpg
CO2 EMISSIONS COMPLIANCE	65 g/km
FUEL SYSTEM	Electronic Injection
COOLING	Forced air
STARTER	Electric
GEARBOX	CVT automatic with torque server
CLUTCH	Automatic dry centrifugal with shock absorbers
LOAD-BEARING STRUCTURE	Sheet steel shell with welded structural reinforcements
FRONT SUSPENSION	Single arm with helical spring and single hydraulic shock absorber
REAR SUSPENSION	Helical spring with preload adjustable (4 positions) and single hydraulic shock absorber
FRONT BRAKE	Stainless steel Ø 200 mm disc with hydraulic control
REAR BRAKE	Ø 140 mm drum with mechanical control
ABS/ASR SYSTEM	ABS at the front wheel only
FRONT TIRE	Tubeless 110/70 - 12"
REAR TIRE	Tubeless 120/70 - 12"
LENGTH/WIDTH/WHEELBASE	73.6 / 28.9 / 52.7 in
SEAT HEIGHT	31.1 in
FUEL TANK CAPACITY	2.1 gal
EMISSIONS COMPLIANCE	Euro 4