

KARAVAN

BOAT

Welded Tubular Frame
for strength and stability

Attractive, durable
17-Step Powder Coat Finish

Reliable
ShortFree™
Lighting
and **Sure-Lube**
systems

QuietTow™ and **SwayControl™**
engineering for carefree towing

KKB-1800-70



SLT-5800-78



KKRT-4800-78




KKB-2400-78




Some models shown with optional features

Find The Right Trailer In 3 Easy Steps

1. Measure the Transom-To-Bow-Eye Length



2. Measure the Bottom Width



3. Calculate Carrying Capacity

$$\text{Carrying capacity} = \left[\text{Boat weight including motor (lb)} + \left(\text{Fuel capacity (gal)} \times 6.3 \text{ lb / gal} \right) \right] \times \begin{cases} 1.07 & \text{if max passenger capacity} \leq 6 \\ 1.10 & \text{if max passenger capacity} > 6 \end{cases}$$

SPECS		BOAT			TRAILER							
		Max Boat Length	Transom to Bow Eye	Max Bottom Width	Overall Length	Overall Width	Width Between Fenders	Trailer Weight	GVWR	Carrying Capacity	Tire Size	Hitch Ball Size
STEEL BUNK	KBE-1250-46	199"	95-182"	47"	217"	59"	47"	250 lb	1500 lb	1250 lb	4.80 x 12B	2"
	KB-1250-56	204"	106-188"	57"	222"	73"	57"	335 lb	1585 lb	1250 lb	5.30 x 12C	2"
	KB-1470-56	204"	106-188"	57"	222"	73"	57"	335 lb	1805 lb	1470 lb	ST175/80D13B	2"
	KBL-1500-56	234"	133-217"	57"	252"	73"	57"	325 lb	1825 lb	1500 lb	ST175/80D13B	2"
	KDB-1500-71	174"	106-156"	68"	192"	85"	68"	410 lb	1910 lb	1500 lb	ST175/80D13B	2"
	KCB-1800-60	210"	163-194"	63"	228"	79"	63"	385 lb	2185 lb	1800 lb	ST175/80D13B	2"
	KKB-1800-70	221"	180-194"	72"	239"	90"	72"	420 lb	2220 lb	1800 lb	ST175/80D13B	2"
	KKB-2400-78	225"	177-191"	80"	243"	99"	80"	550 lb	2950 lb	2400 lb	ST185/80D13C	2"
	KCB-2400-82	223"	188-203"	85"	241"	102"	85"	525 lb	2925 lb	2400 lb	ST185/80D13C	2"
	KCB-3100-78	274"	203-237"	80"	292"	100"	80"	620 lb	3720 lb	3100 lb	ST215/75D14C	2"
	KCBT-4800-78	274"	204-238"	80"	292"	100"	80"	1095 lb	5895 lb	4800 lb	ST215/75D14C	2"
	KKBT-4800-78	279"	208-241"	80"	297"	99"	80"	920 lb	5720 lb	4800 lb	ST215/75D14C	2"
STEEL ROLLER	KKBT-5400-78	306"	218-284"	80"	324"	99"	80"	1020 lb	6420 lb	5400 lb	ST215/75D14C	2"
	KR-1500-56	207"	106-189"	57"	225"	73"	57"	325 lb	1825 lb	1500 lb	5.30 x 12C	2"
	KKR-3100-78-S	248"	176-210"	80"	266"	99"	80"	630 lb	3730 lb	3100 lb	ST215/75D14C	2"
ALUMINUM BUNK	KKRT-4800-78	272"	221-234"	80"	290"	99"	80"	980 lb	5780 lb	4800 lb	ST215/75D14C	2"
	SL-1700-70	225"	166-203"	77"	243"	92"	77"	500 lb	2200 lb	1700 lb	ST175/80D13B	2"
	SL-2450-74	224"	181-193"	82"	242"	97"	82"	510 lb	2960 lb	2450 lb	ST185/80D13C	2"
	SL-4100-78	256"	199-214"	84"	274"	102"	84"	841 lb	4941 lb	4100 lb	ST225/75D15D	2"
	SLT-5800-78	308"	236-286"	82"	326"	102"	82"	1270 lb	7070 lb	5800 lb	ST215/75D14C	2"
	SLT-8600-78	327"	272-288"	81"	345"	102"	81"	1320 lb	9920 lb	8600 lb	ST225/75D15D	2-5/16"

FEATURES

SwayControl™ Engineering

Welded tubular frame and adjustable axle on most models

Durable and Attractive High Quality Finish

Choose either our galvanized or black powder coat

Step Fender / Swing Tongue

Standard on most models

Optional Low Maintenance Disc Brakes

Both single axle and tandem axle disc brakes available

QuietTow™ Componentry

Less noise on spring axle models via nylon bushings

High Reliability ShortFree™ Lighting System

Fully grounded and all plug (no ScotchLoks); wiring is concealed

Sure-Lube Wheel Bearing Grease System

Allows quick and clean greasing for easy maintenance

Coated Self-Coiling Safety Cables

Cables coil out of the way when not in use

KARAVAN

PO Box 27 Fox Lake, WI 53933 fx 920.928.6201
www.karavantrailers.com