



2027 – Xtrainer 200

Specifications



ENGINE

Type	Beta Built single cylinder, 2-stroke, liquid cooled, with BPV power valve system and, electric start with back-up kick starter sold as an option
Bore	62mm
Stroke	63mm
Displacement	190.2cc
Compression Ratio	14.35:1
Exhaust Valve	Beta Progressive Valve (BPV)
Ignition	AC Digital CDI with oil pump controller
Spark Plug	NGK CMR7H
Lubrication	Electronic oil injection
Oil Tank Capacity	650cc
Carburetor	Keihin PWK 36
Clutch	Wet diaphragm style
Transmission	6 Speed
Final Drive	O-ring chain

CHASSIS

Frame	Molybdenum steel / parameter-style double cradle w/ quick air filter access
Wheelbase	57.75"
Seat Height	36"
Ground Clearance	12.6"
Footrest Height	15.3"
Dry Weight	215 lbs (dry weight, no fuel)
Fuel Tank Capacity	2.25 US Gallons
Front Suspension	43 mm hydraulic inverted front fork with adjustable dampening
Rear Suspension	Steel body shock with adjustable rebound and compression
Front Wheel Travel	10.6"
Rear Wheel Travel	10.6"
Front Brake	260 mm floating rotor
Rear Brake	240 mm rotor
Front/Rear Rim	90/90 - 21" (Front) 140/80 - 18" (Rear)
Tire	Soft enduro competition

MSRP \$8,790.00



*Specifications subject to change without notice. Additional information on all models including manuals, accessories, and parts books are available online at www.betausa.com under the support tab.

**This Model is for competition use only

Rideability