PRIMAVERA 150 – TECHNICAL SPECIFICATIONS

ENGINE	Single cylinder 4-stroke, 3 valves, i-get
DISPLACEMENT	155 cc
BORE X STROKE	58 mm x 58.6 mm
MAX POWER AT THE CRANK SHAFT	9.2 kW - 12.5 HP - at 7,750 rpm
MAX TORQUE	12.5 Nm at 6,500 rpm
CONSUMPTION	37 km/l
CO2 EMISSIONS	63 g/km
COMPLIANCE	
FUEL SYSTEM	Electronic injection
COOLING	Forced air
STARTER	Electric
GEARBOX	CVT continuously variable transmission with torque server
CLUTCH	Automatic centrifugal dry clutch with vibration dampers
LOAD-BEARING STRUCTURE	Sheet steel body with welded reinforcements
FRONT SUSPENSION	Single-sided link arm with coil spring and hydraulic monoshock absorber
REAR SUSPENSION	Coil spring with preload adjustable to 4 positions and hydraulic monoshock absorber
FRONT BRAKE	Ø 200 mm stainless steel disc with hydraulic control
REAR BRAKE	Ø 220 mm stainless steel disc with hydraulic control
ABS SYSTEM	Single channel ABS on front wheel
FRONT TYRE	Tubeless 110/70 - 12”
REAR TYRE	Tubeless 120/70 - 12”
LENGTH / WIDTH / WHEELBASE	1,870 / 750 / 1,340 mm
SEAT HEIGHT	785 mm
FUEL TANK CAPACITY	8 litres
EMISSIONS COMPLIANCE	Euro 5+